


SHIELDED DIGITAL AUDIO TRANSFORMER



T500X SERIES



- Shielded Transformer
- Lowest Jitter
- Highest CMR
- 28-192KHz sample rate
- RoHS Compliant Product
- Custom Design Available

ELECTRICAL PARAMETERS @25°C


Part Number	Turns Ratio (1-4:5-8 ±2%)	OCL (μH MIN) 1-4	L_L (μH MAX) 1-4	C_{wv} (pF MAX) 1-8	DC Resistance (Ω MAX) 1-4/5-8	Package
T5004	1:1	600	1.50	100	1.5 & 1.5	SMD
T5005	1:1	600	1.50	100	3.00	Thru Hole

NOTES:


1. OCL measured at 50KHz, 0.25V_{RMS}
2. C_{wv} measured between pin 1 and 8 with pin 2 or 6 to guard voltage
3. Hipot: 2KVDC, 0.5mA max, 3 seconds (1,4 to 5,8)

4. L_L and C_{wv} measured at 100KHz 0.25V_{RMS}
5. Do not ground both pin 2 and pin 6 at the same time
6. Polarity: 1 & 5 are in phase

DIMENSIONS (mm)



SCHEMATIC



Product performance is limited to specified parameters. Data is subject to change without prior notice.

Dimensions
Unless otherwise specified, all tolerances are:
inch: .XX : ±0.015 .XXX : ±0.004
mm: X.X : ±0.38 X,XX : ±0.10

Tel: 310-325-1043
Fax: 310-325-1044

www.mpsind.com
sales@mpsind.com